




Genie® GS™ -3390, GS-4390 & GS-5390

Specifications

Models	GS-3390		GS-4390		GS-5390	
Measurements	US	Metric	US	Metric	US	Metric
Working height max. ⁽¹⁾	39ft	12.06 m	49ft	15.11 m	59ft	18.15 m
A Platform height max.	33ft	10.06 m	43ft	13.11 m	53ft	16.15 m
B Platform height - stowed ⁽²⁾	5ft 1in	1.55 m	5ft 11in	1.80 m	6ft 7.5in	2.02 m
C Platform length - outside	13ft .5in	3.98 m	13ft .5in	3.98 m	13ft .5in	3.98 m
Platform length - Outside, extended single deck	17ft 6.25in	5.34 m	17ft 6.25in	5.34 m	17ft 6.25in	5.34 m
D Platform length - Outside, extended dual deck	21ft 6.5in	6.57 m	21ft 6.5in	6.57 m	21ft 6.5in	6.57 m
E Slide-out platform extension deck - front	5ft	1.52 m	5ft	1.52 m	5ft	1.52 m
F Slide-out platform extension deck - rear	4ft	1.22 m	4ft	1.22 m	4ft	1.22 m
G Platform width - outside	6ft	1.83 m	6ft	1.83 m	6ft	1.83 m
H Height - stowed (folding rails)	8ft 10.5in	2.71 m	9ft 7.5in	2.93 m	10ft 4in	3.15 m
Height - stowed (rails lowered)	6ft 7.75in	2.03 m	7ft 4.75in	2.25 m	8ft 1.25in	2.47 m
Length - stowed, single deck	12ft 11.25in	3.94 m	12ft 11.25in	3.94 m		*
Length - stowed, dual deck	13ft 0.5in	3.98 m	13ft 0.5in	3.98 m		-
Length - stowed, with outriggers	16ft	4.88 m	16ft	4.88 m	16ft	4.88 m
Length - extended, single deck	17ft 8.5in	5.40 m	17ft 8.5in	5.40 m	17ft 8.5in	5.40 m
Length - extended, dual deck	21ft 6.5in	6.57 m	21ft 6.5in	6.57 m	21ft 6.5in	6.57 m
I Width (standard tires)	7ft 8in	2.34 m	7ft 8in	2.34 m	7ft 8in	2.34 m
J Wheelbase	9ft 4in	2.84 m	9ft 4in	2.84 m	9ft 4in	2.84 m
K Ground clearance (center)	1ft 2in	36 cm	1ft 2in	36 cm	1ft 2in	36 cm



Productivity

	7/7		7/7		7/7	
Max. platform occupancy (in/out)						
Lift capacity	2,500 lb	1,134 kg	1,500 lb	680 kg	1,500 lb	680 kg
Lift capacity - extension deck extended	500 lb	227 kg	500 lb	227 kg	500 lb	227 kg
Max. platform drive height	33ft	10.06 m	43ft	13.11 m	30ft	9.14 m
Drive speed - stowed	5.0 mph	8.0 km/h	5.0 mph	8.0 km/h	5.0 mph	8.0 km/h
Drive speed - raised	0.7 mph	1.1 km/h	0.7 mph	1.1 km/h	0.7 mph	1.1 km/h
Gradeability - stowed ⁽³⁾	50%		50%		40%	
Turning radius - inside/outside	7ft 1in/17ft 6in	2.16m/5.33m	7ft 1in/17ft 6in	2.16m/5.33m	7ft 1in/17ft 6in	2.16m/5.33m
Lifting speed - raise/lower	45/29sec		45/39sec		60/49sec	
Max. outrigger leveling (front to back /side to side)	7°/12°		7°/12°		7°/12°	

Drive

Tires - Foam-filled rough terrain	12×33in	30×84 cm	12×33in	30×84 cm	12×33in	30×84 cm
-----------------------------------	---------	----------	---------	----------	---------	----------

Power

Power	Diesel		Diesel		Diesel	
Fuel Tank	20 gal	75.7 L	20 gal	75.7 L	20 gal	75.7 L
Hydraulic tank capacity	30 gal	113.6 L	30 gal	113.6 L	30 gal	113.6 L
Weight	11,977 lb	5,433 kg	12,894 lb	5,849 kg	16,567 lb	7,515 kg
Weight with outriggers	13,652 lb	6,195 kg	14,611 lb	6,628 kg	16,567 lb	7,515 kg
Additional weight, optional dual deck	784 lb	356 kg	784 lb	356 kg	784 lb	356 kg
Additional weight, optional super deck	906 lb	411 kg	906 lb	411 kg	906 lb	411 kg
Additional weight, optional generator	105 lb	48 kg	105 lb	48 kg	105 lb	48 kg
Tire load max.	4,734 lb	2,147 kg	4,722 lb	2,142 kg	5,294 lb	2,401 kg
Tire contact pressure - front, platform fully extended	115.5 psi	796 kPa	115.2 psi	794 kPa	129.1 psi	890 kPa
Occupied floor pressure	167 psf	8.00 kPa	167 psf	7.98 kPa	187 psf	8.94 kPa

Sound and Vibration Levels

Sound Pressure level (ground workstation)	< 88 dBA		< 88 dBA		< 88 dBA	
Sound Pressure level (platform workstation)	< 78 dBA		< 78 dBA		< 78 dBA	
Vibrations	< 8 ft 2in/s ²	< 2.5 m/s ²	< 8 ft 2in/s ²	< 2.5 m/s ²	< 8 ft 2in/s ²	< 2.5 m/s ²

(1) The metric equivalent of working height adds 2m to platform height. US adds 6ft to platform height.

(2) Based on RT tires; deduct 2in/5.8cm for turf and non-marking tires.

(3) Gradeability applies to driving on slopes and may vary depending on options and machine configurations. See operator's manual for details regarding slope ratings.

(4) Weight refers to standard configuration and may vary depending on options and/or country standards.

(5) Floor loading information is approximate and may vary depending on options and machine configurations. It should be used only with adequate safety factors.

* GS-5390 comes standard with outriggers. Machine length with outriggers represents overall length.



760 rue Bériault, Longueuil, Québec (Canada) J4G 1R8
1-833-360-3330 | info@sosequipment.ca



Genie® GS™ -3390, GS-4390 & GS-5390

SKU: Standard Model

- GS-3390, Oscillating Axle
- **GS439001AD0001:** GS-4390, 2kW AC Generator 110V/60Hz

* Build to Order

SKU: Standard Model

- **GS539001AF0001:** GS-5390, Auto leveling outriggers
- **GS539001AE0031:** GS-5390, Auto leveling outriggers, 2kW AC Generator 110V/60Hz
- **GS539001AE0030:** GS-5390, Ford Gas/LPG, Auto leveling outriggers

Option availability		S	S+	BtO
Power	48.7 hp, 36.3kW, Deutz D2.9L, Diesel, T4f			<input type="radio"/>
	60 hp, 44.7kW, Ford 2.5L, Gas/LPG		<input checked="" type="checkbox"/>	
	Cold weather package			<input type="radio"/>
Platform	2kW AC Generator, 110V/60Hz			<input type="radio"/>
	AC power to platform		<input checked="" type="checkbox"/>	
	Air line to platform			<input type="radio"/>
	Diamond plate platform deck		<input checked="" type="checkbox"/>	
	Dual slide-out extension deck			<input type="radio"/>
	Electronic horn		<input checked="" type="checkbox"/>	
	Folding rails, Full-height swing gate		<input checked="" type="checkbox"/>	
	Lanyard attachment points		<input checked="" type="checkbox"/>	
	Platform control guard (PCON)		<input checked="" type="checkbox"/>	
	Platform control with fault indicator		<input checked="" type="checkbox"/>	
	Platform load sense system		<input checked="" type="checkbox"/>	
	Proportional drive and lift		<input checked="" type="checkbox"/>	
	Self-closing entry gate		<input checked="" type="checkbox"/>	
	Single slide-out extension deck		<input checked="" type="checkbox"/>	
Chassis	4 wheel drive		<input checked="" type="checkbox"/>	
	Active oscillating axle			<input type="radio"/>
	Auto leveling hydraulic outriggers			<input type="radio"/>
	Biodegradable hydraulic oil			<input type="radio"/>
	Cold weather hydraulic oil			<input type="radio"/>
	Descent, tilt and motion alarm		<input checked="" type="checkbox"/>	
	Dual LED flashing beacons		<input checked="" type="checkbox"/>	
	High floatation, foam-filled tires		<input type="radio"/>	<input type="radio"/>
	Hydraulic oil cooler			<input type="radio"/>
	LPG tank 33.5 lb		<input type="radio"/>	<input type="radio"/>
	Lift Connect Telematics		<input type="radio"/>	<input type="radio"/>
	Lift Connect with Access Manager upgrade		<input type="radio"/>	<input type="radio"/>
Rough Terrain, foam-filled tires		<input checked="" type="checkbox"/>		
Rough Terrain, foam-filled, non-marking tires		<input type="radio"/>	<input type="radio"/>	

- S Standard
- S+ Standard +
- BtO Build to Order
- ✓ Standard Features
- Options



4 Wheel Drive



Optional Oscillating axle



Slide-Out Engine Tray



Genie Genuine Accessories⁽¹⁾

- Lift Tools Productivity Tools
- Lift Connect Telematics
- Tech Pro Link Handheld Device

(1) More accessories available from Genie Genuine Parts.



760 rue Bériault, Longueuil, Québec (Canada) J4G 1R8
1-833-360-3330 | info@sosequipment.ca

Product specifications are subject to change without notice or obligation. Photographs and/or drawings herein are for illustrative purposes only. Refer to the appropriate Operator's Manual for instructions on proper equipment use. Failure to follow instructions in the Operator's Manual may result in serious injury or death. The only warranty applicable to our equipment is the standard written warranty applicable to the particular product and sale and we make no other warranty, express or implied. Products and services listed may be trademarks, service marks or trade names of Terex Corporation and/or their subsidiaries in the USA and many other countries. Terex, Genie, Quality By Design, Xtra Capacity, Lift Power, Lift Guard, Lift Tools, Lift Connect and Tech Pro Link are registered trademarks of Terex Corporation or its subsidiaries.

